

AMPLIDECT295™

Amplified Cordless Telephone with Integral
Answering Machine



CALLING/TALKING

- → HAC
- → Adjustable receiving volume: up to 30dB
- Speaker phone
- Adjustable speaker volume
- Phonebook up to 50 numbers
- Redial function for last 10 outgoing calls
- → P/T dialing mode
- R button for call waiting
- Hotkey to phonebook
- Hotkey to menu
- → Flash function (100ms/300ms/600ms)
- Large keys

HANDSET LCD DISPLAY

- White backlight
- Choice of 7 languages (English, German, French, Italian, Dutch, Spanish and Russian)
- Dimensions: 40x40mm
- → Display: Alphanumeric / 4 lines / Characters size : 7mm
- Clock
- Alarm
- > Key lock
- Message waiting icon
- Communication time indication

CALLER ID *

- Name presentation in hook mode (type 1) and conversation mode (type 2):
 - o 20 incoming numbers
 - o 10 outgoing numbers
- Caller ID also for Call waiting
- > Possibility to transfer a call received to the directory
- Indicator call waiting
- Indicator new call

ANSWERING MACHINE

- 15 minutes of recording time
- 2 announcements
- 2 answering machine modes (simple answering machine and answering machine recorder)
- Visual info. on the base about number of messages
- → 4-digit user selectable remote codes
- Remote control for messages on handset
- Erase each/all messages
- Audible time & date stamp on recorded messages
- 3 languages (English, German and French)

MULTI HANDSET

- Handset locator
- 3-way conference with privacy protection
- Up to 4 bases and up to 5 handsets
- Call transfer of external calls (when using several handsets)
- Intercom between handset



RINGER

- → Extra loud ringtones: up to 75dB on the handset and 80dB on the base
- → 5 polyphonic ringtones and 5 normal
- Adjustable ring volume (Mute + 5 positions)
- Customizable ringtones for phonebook contacts
- Ringer indicator

TECHNICAL SPECIFICATIONS

- → 1 battery ni-Mh 2.4V 500mA (included)
- Memory storage
- Power supply by AC adapter (supplied)
- Dial/Decimal voice frequency
- > Standby time: 2 days
- Continuous talk time: 8 hours
- GAP compliant
- Range:
 - $_{\circ}$ Indoor: up to 50m
 - Open field: up to 300m
- Dimensions:
 - o Handset:172x55x25 mm
 - o Base: 136x91x105 mm

OPTIONAL EXTRA

- AmpliDect295 AD
- → PhotoDect295



AmpliDect295 AD

PhotoDect295

FAMILY PRODUCTS

- AmpliDect295 DUO
- AmpliDect Combi 295
- AmpliDect Combi Photo 295
- → AmpliDect295 SOS-PRO
- AmpliDect295 Photo

