

# AMPLIDECT COMBI 295

**Double Corded and Cordless Telephone with Answering Machine** 

CUNUSS

......

8

0328587599

Ģ

2ABC 3 DEF

5 JKL 6MNG

8TUV 9WAY

0 #

m

R

M ?



DDD

## **CALLING/TALKING**

- Hearing Aid Compatible
- → Adjustable receiving volume control (up to 30dB)
- → 4 one-touch memories whose 3 with pictures
- Speaker phone
- → Redial function for last 10 outgoing calls
- ➔ 50 phonebook memories
- → Mute/Pause function
- Keyboard
  - Large keys (25x14mm) 0
  - Big characters (10mm) 0

## HANDSET AND BASE LCD DISPLAY

- → Large screen
- → White backlight
- → Choice of 7 languages on the handset (English, German,
- French, Italian, Dutch, Spanish and Russian)
- → Choice of 6 languages on the base (English, German,
- French, Italian, Spanish and Russian)
- Navigation manu
- Time stamping
- → Alarm
- → Key lock
- Communication time indication ->

## **ANSWERING MACHINE**

- ➔ 15 minutes of recording time
- → On/Off key
- → 2 announcements
- → 2 answering machine modes (simple answering machine and answering machine recorder)
- ➔ Visual info. on the base about number of messages
- ➔ 4-digit user selectable remote codes
- Remote control for messages on handset
- Erase each/all messages
- Audible time & date stamp on recorded messages
- ➔ 3 languages (English, German and French)
- ➔ Note recorder

Choice of the number of ringtones for the release of the → answering machine.

## **MULTI HANDSET**

- → Handset locator
- → 3-way conference with privacy protection
- → Conference between the base and the handset
- → Up to 4 bases and up to 4 handsets
- **→** Call transfer of external calls (when using several handsets)
- → Intercom between handset

## RINGER

- → 10 ringtones for the base and 10 ringtones for the handset
- Adjustable ring volume (Mute + 5 positions) -
- Strobe visual ringer indicator on the base and on the → handset
- → Ringtone volume :
  - 80dB on the base 0
    - 75dB on the handset 0

## **TECHNICAL SPECIFICATIONS**

- → 1 battery ni-Mh 2.4V 500mA (included)
- Memory storage
- Power supply by AC adapter (supplied)
- Dial/Decimal voice frequency
- → Wall mountable
- → GAP compliant
- → Range :
  - Indoor : up to 50m 0
  - Open field : up to 300m  $\cap$

## CALLER ID \* (HANDSET + BASE)

→ Name presentation in hook mode (type 1) and conversation mode (type 2)

- 20 incoming numbers 0
- Caller ID also for Call waiting ->
- ➔ Indicator call waiting
- -Indicator new call

## **ADDITIONAL HANDSETS**

→ AmpliDect295 AD PhotoDect295

**FAMILY PRODUCTS :** 

AmpliDect295

AmpliDect295 DUO

AmpliDect Combi Photo 295

- AmpliDect295 AD
- PhotoDect295
- AmpliDect295 SOS-PRO
  - AmpliDect295 Photo
- eemarc **Telecom SA** www.geemarc.com

\*To use the CID facility it will be necessary to subscribe to your network provider's CID service Items pictured and details are subject to change at the manufacturer's discretion.

