AMPLIDECT295-2™

Amplified Cordless Telephone with Integral Answering Machine With Two Handsets

CALLING/TALKING

- HAC
- Adjustable receiving volume: up to **30dB**
- Speaker phone
- Adjustable speaker volume
- Phonebook up to 50 numbers
- Redial function for last 10 outgoing calls
- P/T dialing mode
- R button for call waiting
- Hotkey to phonebook
- Hotkey to menu
- Flash function (100ms/300ms/600ms)
- Large keys

HANDSET LCD DISPLAY

- White backlight
- Choice of 7 languages (English, German, French, Italian, Dutch, Spanish and Russian)
- Dimensions: 40x40mm
- Display: Alphanumeric / 4 lines / Characters size: 7mm
- Clock
- Alarm
- Key lock
- Message waiting icon
- Communication time indication

CALLER ID *

- Name presentation in hook mode (type 1) and conversation mode (type 2):
  - 20 incoming numbers
  - 10 outgoing numbers
- Caller ID also for Call waiting
- Possibility to transfer a call received to the directory
- Indicator call waiting
- Indicator new call

ANSWERING MACHINE

- 15 minutes of recording time
- 2 announcements
- 2 answering machine modes (simple answering machine and answering machine recorder)
- Visual info. on the base about number of messages
- 4-digit user selectable remote codes
- Remote control for messages on handset
- Erase each/all messages
- Audible time & date stamp on recorded messages
- 3 languages (English, German and French)

MULTI HANDSET

- Handset locator
- 3-way conference with privacy protection
- Up to 4 bases and up to 5 handsets
- Call transfer of external calls (when using several handsets)
- Intercom between handset

RINGER

- Extra loud ringtones: up to **75dB** on the handset and **80dB** on the base
- 5 polyphonic ringtones and 5 normal
- Adjustable ring volume (Mute + 5 positions)
- Customizable ringtones for phonebook contacts
- Ringer indicator

TECHNICAL SPECIFICATIONS

- 1 battery ni-Mh 2.4V 500mA (included)
- Memory storage
- Power supply by AC adapter (supplied)
- Dial/Decimal voice frequency
- Standby time: 2 days
- Continuous talk time: 8 hours
- GAP compliant
- Range:
  - Indoor: up to 50m
  - Open field: up to 300m
- Dimensions:
  - Handset:172x55x25 mm
  - Base: 136x91x105 mm

OPTIONAL EXTRA

- AmpliDect295 AD
- PhotoDect295

AmpliDect295 AD

PhotoDect295

FAMILY PRODUCTS

- AmpliDect295 DUO
- AmpliDect Combi 295
- AmpliDect Combi Photo 295
- AmpliDect295 SOS-PRO
- AmpliDect295 Photo

**To use the CID facility it will be necessary to subscribe to your network provider's CID service*

Items pictured and details are subject to change at the manufacturer's discretion.

geemarc™ Telecom SA

www.geemarc.com