

AMPLIDECT295-2™

Amplified Cordless Telephone with Integral Answering Machine With Two Handsets

R

Ģ

5 . 6.

0 #*

1)

8TUN 9WXY

2480 300

2



CALLING/TALKING

- HAC
- Adjustable receiving volume: up to 30dB
- Speaker phone
- Adjustable speaker volume
- Phonebook up to 50 numbers
- → Redial function for last 10 outgoing calls
- P/T dialing mode
- R button for call waiting
- Hotkey to phonebook
- Hotkey to menu
- Flash function (100ms/300ms/600ms)
- Large keys

HANDSET LCD DISPLAY

- White backlight
- Choice of 7 languages (English, German, French, Italian, Dutch, Spanish and Russian)
- Dimensions: 40x30mm
- Display: Alphanumeric / 4 lines / Characters size: 7mm
- Clock
- 🔶 Alarm
- Key lock
- Message waiting icon
- Communication time indication

CALLER ID *

- Name presentation in hook mode (type 1) and conversation mode (type 2):
 - 20 incoming numbers
 - 10 outgoing numbers
- Caller ID also for Call waiting
- → Possibility to transfer a call received to the directory
- Indicator call waiting
- Indicator new call

ANSWERING MACHINE

- ➔ 15 minutes of recording time
- ➔ 2 announcements
- 2 answering machine modes (simple answering machine and answering machine recorder)
- Visual info. on the base about number of messages
- ➔ 4-digit user selectable remote codes
- Remote control for messages on handset
- Erase each/all messages
- Audible time & date stamp on recorded messages
- ➔ 3 languages (English, German and French)

MULTI HANDSET

- Handset locator
- ➔ 3-way conference with privacy protection
- Up to 4 bases and up to 5 handsets
- Call transfer of external calls (when using several handsets)
- ➔ Intercom between handset

RINGER

2

2100 300

5 . 6.

8TU 9.

#×

0

ID R

- Extra loud ringtones: up to 75dB on the handset and 80dB on the base
- ➔ 5 polyphonic ringtones and 5 normal
- Adjustable ring volume (Mute + 5 positions)

Deemarc

- Customizable ringtones for phonebook contacts
- Ringer indicator

TECHNICAL SPECIFICATIONS

- → 1 battery ni-Mh 2.4V 500mA (included)
- Memory storage
- Power supply by AC adapter (supplied)
- Dial/Decimal voice frequency
- Standby time: 2 days
- Continuous talk time: 8 hours
- GAP compliant
- Range:
 - Indoor: up to 50m
 - Open field: up to 300m
- Dimensions:
 - Handset:172x55x25 mm
 - Base: 136x91x105 mm

OPTIONAL EXTRA

- AmpliDect295 AD
- PhotoDect295



AmpliDect295 SOS-PRO

AmpliDect295 Photo

PhotoDect295

FAMILY PRODUCTS

- AmpliDect295 DUO
- AmpliDect Combi 295
- AmpliDect Combi Photo 295
- Telecom SA

*To use the CID facility it will be necessary to subscribe to your network provider's CID service Items pictured and details are subject to change at the manufacturer's discretion.

