<u>leemarc</u>™ Hear the Difference

CALLING/TALKING (Base)

- Hearing Aid Compatible
- → Adjustable receiving volume control (up to 30dB on base and both handsets)
- ➔ 4 one-touch memories, 3 with pictures
- Speaker phone
- Redial function for last 10 outgoing calls
- ➔ 50 phonebook memories

0

- Mute/Pause function
- Keyboard
- Large keys (25x14mm)
- Big characters (10mm) 0

LCD DISPLAYS

- Large screens (80*43mm-3 lines on the base, -> 40*30mm-1 line on the handset)
- -White backlight
- -> Choice of 7 languages on the handset (English, German, French, Italian, Dutch, Spanish and Russian)
- -> Choice of 6 languages on the base (English, German, French, Italian, Spanish and Russian)
- -> Navigation menu
- -> Time stamping
- -> Alarm
- ➔ Key lock
- Talk time indication -

ANSWERING MACHINE

- ➔ 15 minutes of recording time
- → On/Off key
- → 2 announcements (message record or no message record option)
- 2 answering machine modes
- Visual info. on the base about number of messages
- ➔ 4-digit user selectable remote codes
- → Remote control for messages on handset
- ➔ Erase each/all messages
- → Time & date stamp on recorded messages
- → 3 languages (English, German and French)
- → Voice memo recoder
- -> Choice of the number of ringtones before answering machine answers

MULTI HANDSET

- -> Handset locator
- -> Conference between the base and the handset
- -> Up to 4 bases and up to 5 handsets
- -> Call transfer of external calls (when using several handsets)
- -> Intercom between handset

PHOTODECT295 (Handset)

- Hearing aid compatible →
- -> Adjustable receiving volume: up to 30dB
 - 4 one-touch photo keys:
 - 0 Large photo keys: 3 x 2 cm
- -> Adjustable speaker phone volume
- → Automatic hang up / on hook
- → DECT phone

-

- -> Recharging base (included)
- -> Speakerphone

RINGER

- → 10 ringtones for the base, 10 ringtones for the handset and 1 ringtone for the photo handset
- -> Adjustable ring volume (Mute + 5 positions)
- → Visual ringer indicator on the base and on the handset
- Ringtone volume:
 - 80dB on the base
 - 75dB on both handsets 0

TECHNICAL SPECIFICATIONS

- **→** 2 batteries ni-Mh 2.4V 500mA (included)
- -> Memory storage
- → Power supply by AC adapter (supplied)
- → Dial/Decimal voice frequency
- → Main phone wall mountable
- → GAP compliant
- → Standby time: 2 days
- -> Talk time: 8 hours
- -Range:
 - Indoor: up to 50m 0
 - Open field: up to 300m 0

CALLER ID *

- -> Name presentation in hook mode (type 1) and conversation mode (type 2) 20 incoming numbers
- → Caller ID also for Call waiting
- → Indicator call waiting
- -Indicator new call

ADDITIONAL HANDSETS

- -AmpliDect295 AD
- PhotoDect295



- **FAMILY PRODUCTS**
- -> AmpliDect295
- -> AmpliDect295 DUO
- -> AmpliDect Combi 295
- AmpliDect Combi Photo 295
- AmpliDect295 SOS-PRO AmpliDect295 Photo
 - eemarc Telecom SA .geemarc.com

*To use the CID facility it will be necessary to subscribe to your network provider's CID service Items pictured and details are subject to change at the manufacturer's discretion.







Aee

SOS

14









0328587599.

2.00 300

5 m 6m

8 TUY 9 War

* on 0 #×

00 R

28587594