



SOS Bracelet

CALLING/TALKING

- Hearing Aid compatible (T position)
- Adjustable receiving volume up to **40dB**
- Adjustable receiving tone control with 5 levels
- 3 direct photo memories (photo keys)
- 10 indirect memories
- Phonebook: 30 numbers (with talking caller ID)
- Blacklist: possibility to block up to 200 numbers
- 4 call blocking modes: block all numbers / block blacklisted numbers only / block international and private numbers / deactivate call blocking
- SOS button
- Using a 4-digit pin code, the people calling you can make so that their calls are automatically answered.
- Flash (100/270/600mS)
- Two-way speakerphone with LED display
- Adjustable receiving volume when on speakerphone
- Call waiting button
- Pause function
- Last 10 outgoing numbers redial
- Large alphanumeric display with white backlight
- 6 languages: French, English, German, Dutch, Italian, and Spanish
- Voice assistance (keys, menu, phonebook, telephone number)

LCD SCREEN

- Large backlit LCD screen
- 4-line LCD display
- Automatic time and date setting
- 16-digit number, 16-character name
- Icon for unread messages on the answering machine

CALLER ID *

- Caller identification and call waiting
- Talking keypad and CID
- Name & phone number
- Calls received display with date and time

EMERGENCY CALL FUNCTION

- Emergency contacts are called when the SOS button is pressed on the telephone or the SOS button on the bracelet
- SOS procedure to automatically dial the numbers of up to 5 people + emergency voice message
- SOS function activation confirmation tone
- Personalised voice announcement
- Ambient temperature alarm: automatic activation of the SOS function (5 emergency numbers dialed + voice message) when excessively low or high temperatures are detected (adjustable thresholds from 5°C to 20°C for the minimum and from 25°C to 50°C for the maximum)
- Input for external sensor (2 contacts, 2.5mm connector), SOS function with 3 modes (off, normal, 24h), detection of either opened or closed contact

RINGER

- Extra bright visual ring indicator
- 10 melodies
- Adjustable ringer volume: Off / Volume 1 / Volume 2 / Volume 3
- Extra Loud Ringer (up to approx. 85dB at 1metre)

TECHNICAL SPECIFICATION

- Wall mountable
- Dimensions: 18,5 x 20 x 5 cm
- Rechargeable battery - AAx4 not included

BOX CONTENT

- 1 x SERENITIES 100
- 1 x AC- DC adaptor
- 1 x 3.5mm jack cable, 4 contacts
- 1 x Fully modular 7ft line cord RJ11/RJ11 plug
- 1 x Fully modular 9ft curly cord RJ9 plug

OPTIONAL EXTRAS

- Additional SOS Bracelets (869,2MHz)
- SOS and fall detection bracelets (VBC10)